

Fluids and Capacities

Recommended Fluids

! To achieve the required high performance of synthetic lubricants, do not mix with mineral oils.

Engine Oil: Mobil 1 0W-40. However, if this oil is not available a fully synthetic 0W-40 oil meeting the specifications detailed below can be used. No other viscosity grades or specifications are acceptable.

Authority	Standard
API	SL / SJ / EC / CF
ACEA	A3 / B3 / B4
ILSAC	GF3

! Do not mix OAT antifreeze with glycol based antifreeze.

Engine Coolant: 50% water, 50% Havoline OAT

Automatic Transmission Fluid: Shell ATF L10108

Automatic Transmission Final Drive Oil: Millers TRX1219M 75W90

12.8

Brake Fluid: React Performance DOT 4

Power Steering Fluid: Pentosin CHF-11S

Air Conditioner Refrigerant: HFC134A

Capacities

Engine Sump (including filter): 13.1 litres

Automatic Final Drive and Cooler: 1.6 litres

Automatic Gearbox and Cooler: 11.4 litres

Engine Cooling System: 15 litres

Power Steering Reservoir: 1.3 litres

Screen Washer Reservoir: 6.9 litres

Fuel Tank: 90.5 litres (Approximately 88.5 litres usable.)



ASTON MARTIN